Change information:

Chap. /page	**Description** (changes to the previous edition)	**Modification no.**
4 /13	Helical-worm gear units adaptation (S.., HS..)	201032
5 /16	Helical-worm gear units (S.7p) added	
10 /22	MGF..-C /PG included	

Für diese technischen Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

SEW-EURODRIVE GmbH & Co KG · D-76642 Bruchsal Tel. (07251) 75-0 · Fax (07251) 75-1970 · http://www.sew.de

Table of contents

1. Introduction/area of application 3
1.1. Explanations of the structure of the tables 3
1.2. Explanations on the individual lubricants 5
1.3. Lubricant change intervals 5
1.4. Compatibility of lubricants with radial oil seals 6
2. Helical gear units (R..), helical-bevel gear units (K.7), parallel-shaft helical gear units (F..) 7
3. Helical-bevel gear units (K.9) 11
4. Helical-worm gear units (S.., HS..) 12
5. Helical-worm gear units (S.7p) 16
6. Spiroplan gear units (W.., HW..) 17
7. PS.F gear units 18
8. PS.C gear units 19
9. BS.F gear units 19
10. MGF gear units (MGF..-B, MGF..-C, MGF..-DSM, MGF../PG) 20

Für diese technischen Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

1. Introduction/area of application

This document describes the approved/recommended lubricants for SEW gear unit series. The approvals/ recommendations are worldwide valid.
If other lubricants are used in the gear units and/or lubricants are used with other temperature ranges than the ones recommended, the right to claim under warranty will become invalid.
Lubricants for standard gear units are subject to approval, the approval will be made according to the document 07004__13 "Supplier approval for qualification and approval of lubricants – gear unit oils" in its current version.

NOTE: Printed documents may not include the latest changes. For the latest version of this document, refer to https://www.sew-eurodrive.de/lubricants.

1.1. Explanations of the structure of the tables



Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
R.. RES K..7 KES HK.. F..	Standard -15 … 40		CLP	VG 220	-15 +80 SEW GearOil Base 220 E1 / US1 SEW 070040313		-15 +80 Optigear BM 220	-15 +80 Renolin CLP 220 Plus SEW 070040313	-15 +80 Mobilgear 600 XP 220 SEW 070040013	-15 +80 Klüberoil GEM 1-220 N	-15 +80 Shell Omala SG 220	-15 +80 Carter EP 220
	-20 … 30			VG 150	-20 +80 SEW GearOil Base 150 E1 / US1* SEW 070040313		-20 +80 Optigear BM 150	-20 +80 Renolin CLP 150 Plus SEW 070040313	-20 +80 Mobilgear 600 XP 150 SEW 070040013	-20 +80 Klüberoil GEM 1-150 N	-20 +80 Shell Omala SG 150	-20 +80 Carter EP 150
	Standard -15 … 40		CLP - PSS	VG 220	-15 +80 SEW GearOil Base 220 E1 / US1 SEW 070040313			-15 +80 Renolin CLP 220 Plus SEW 070040313	-15 +80 Mobilgear 600 XP 220 SEW 070040013			
	-20 … 30			VG 150	-20 +80 SEW GearOil Base 150 E1 / US1* SEW 070040313			-20 +80 Renolin CLP 150 Plus SEW 070040313	-20 +80 Mobilgear 600 XP 150 SEW 070040013			

The specified **ambient (environment) temperatures** are **rough guide values for a preselection** of a suitable lubricant. The exact upper and lower temperature limit for the project planning must be taken from the table with the corresponding trade name! Please note during project planning that the starting behavior may change with low temperatures due to the increasing viscosity.

Für diese technischen Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

Abbreviations:

	Synthetic lubricant
	Mineral lubricant
CLP	Mineral oil
CLP PG	Polyglycol (PG)
CLP HC	Synthetic hydrocarbons – polyalphaolefins (PAO)
E	Oil based on esters
	Lubricant suitable for ATEX environment
	Lubricant for the food processing industry and feed industry. Oils are NSF-H1 registered and compliant according to FDA 21 CFR § 178.3570.
	Easily biodegradable oil for environmentally sensitive areas
1)	Helical-worm gear units with CLP-PG: contact SEW-EURODRIVE
2)	Low-viscosity grease
3)	Ambient temperatures up to -40 °C can be implemented with appropriate measures. Please contact SEW-EURODRIVE.
RWDR	Radial oil seal
PSS	Radial oil seal type PSS (Premium Sine Seal). The addendum "PSS" at the lubricant type signals compatibility with the sealing system. Lubricants with the addendum PSS in brackets are compatible both with conventional oil seals and PSS.

Für diese technischen Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

1.2. Explanations on the individual lubricants



* The service life will be considerably reduced when exceeded. Observe the lubricant change intervals according to chapter 1.3.

1.3. Lubricant change intervals

The following image depicts the change intervals for standard gear units under normal ambient conditions. In case of special designs under severe/aggressive ambient conditions, change the lubricant more frequently.
Notice: Filling of wrong lubricant may lead to a loss of the lubricant properties and thus damage the gear unit.
Do not mix synthetic lubricants and mineral lubricants. In general, the guideline FVA 606 must be adhered to.



[1] Operating hours
[2] Sustained oil bath temperature
Average value per oil type at 70 °C
[3] CLP PG/CPL PG NSF H1
[4] CLP HC/CLP HC NSF H1
[5] CLP (CC)/E
[6] SEW GearOil Base
[7] SEW GearOil Poly
[8] SEW GearOil Synth

Für diese technischen Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

1.4. Compatibility of lubricants with radial oil seals

SEW07004__13: A lubricant especially recommended by SEW-EURODRIVE, also in regard of compatibility with the approved oil seals. The lubricant exceeds the state-of-the-art requirements.

Approved application temperature range of the oil seals

Oil seal material class	Approved oil sump temperature
NBR	-40 °C ... +80 °C
FKM	-25 °C ... +115 °C
FKM-PSS	-25 °C ... +115 °C

In the low temperature range, oil seals can withstand shaft deflections (e. g. through overhung load) only to a limited extent. Especially avoid or limit pulsating or changing radial displacements of the shaft. Please contact SEW-EURODRIVE if required.

Limitations of use of radial oil seals with the specific lubricant are indicated in the following table:

	Material class		Manufacturer		Material
S	1 NBR	1	Freudenberg		72 NBR 902
		2	Trelleborg		4NV11
	2 FKM	1	Freudenberg	1	75 FKM 585
				2	75 FKM 170055
		2	Trelleborg	1	VCBVR

Example 1:

S11 - Only the elastomer Freudenberg 72 NBR 902 meets the requirements of the SEW-EURODRIVE approval in regard of the specific lubricant.

Example 2:

S2 - Only the elastomer FKM meets the requirements of the SEW-EURODRIVE approval in regard of the specific lubricant.

Für diese technischen Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

2. Helical gear units (R..), helical-bevel gear units (K.7), parallel-shaft helical gear units (F..)

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
R.. RES K..7 KES HK.. F..	Standard -15 40		CLP	VG 220	-15 +80 SEW GearOil Base 220 E1 / US1 SEW 070040313		-15 +80 Optigear BM 220	-15 +80 Renolin CLP 220 Plus SEW 070040313	-15 +80 Mobilgear 600 XP 220 SEW 070040013	-15 +80 Klüberoil GEM 1-220 N	-15 +80 Shell Omala SG 220	-15 +80 Carter EP 220
	-20 30			VG 150	-20 +80 SEW GearOil Base 150 E1 / US1* SEW 070040313		-20 +80 Optigear BM 150	-20 +80 Renolin CLP 150 Plus SEW 070040313	-20 +80 Mobilgear 600 XP 150 SEW 070040013	-20 +80 Klüberoil GEM 1-150 N	-20 +80 Shell Omala SG 150	-20 +80 Carter EP 150
	Standard -15 40		CLP - PSS	VG 220	-15 +80 SEW GearOil Base 220 E1 / US1 SEW 070040313			-15 +80 Renolin CLP 220 Plus SEW 070040313	-15 +80 Mobilgear 600 XP 220 SEW 070040013			
	-20 30			VG 150	-20 +80 SEW GearOil Base 150 E1 / US1* SEW 070040313			-20 +80 Renolin CLP 150 Plus SEW 070040313	-20 +80 Mobilgear 600 XP 150 SEW 070040013			

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well!

* Viscosity as US version available on request.

 Für diese Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

Supplier Approval

SEW drives of the series

R../ K.7/ F../ K.9/ S../ HS../ W../ HW../ PS.F/ PS.C/ BS.F/ MGF..

Lubricant approvals – latest version: www.sew-eurodrive.de/lubricants

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
R.. RES K..7 KES HK.. F..	Standard -25 / 80	Ex	CLP PG	VG 220	-25 / +115 SEW GearOil Poly 220 E1 SEW 070040313		-25 / +115 Optigear Synthetic 800/220	-25 / +115 Renolin PG 220	-25 / +115 Mobil Glygoyle 220	-25 / +115 Klübersynth GH 6-220	-25 / +115 Shell Omala S4 WE 220	-25 / +115 Carter SY 220
	-30 / 70			VG150	-30 / +115 SEW GearOil Poly 150 E1 SEW 070040313					-30 / +115 Klübersynth GH 6-150		
	Standard -25 / 80	Ex	CLP PG - PSS	VG 220	-25 / +115 SEW GearOil Poly 220 E1 SEW 070040313					-25 / +115 Klübersynth GH 6-220		
	-30 / 70			VG150	-30 / +115 SEW GearOil Poly 150 E1 SEW 070040313					-30 / +115 Klübersynth GH 6-150		
	Standard -25 / 40		CLP PG-NSF H1 (-PSS)	VG 220	-25 / +95 SEW GearOil Poly 220 H1 E1 SEW 070040313					-25 / +95 Klübersynth UH1 6-220		
	-20 / 80			VG 460	-20 / +115 SEW GearOil Poly 460 H1 E1 SEW 070040313					-20 / +115 Klübersynth UH1 6-460		
	-30 / 30	Ex		VG 150	-30 / +80 SEW GearOil Poly 150 H1 E1 SEW 070040313					-30 / +80 Klübersynth UH1 6-150		

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well!

 Für diese Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

Supplier Approval

SEW drives of the series

R../ K.7/ F../ K.9/ S../ HS../ W../ HW../ PS.F/ PS.C/ BS.F/ MGF..

Lubricant approvals – latest version: www.sew-eurodrive.de/lubricants

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
R.. RES K..7 KES HK.. F..	Standard -25 / 60	Ex	CLP HC	VG 220[3]	-30 / +110 SEW GearOil Synth 220 E1 SEW 070040313			-25 / +110 Renolin Unisyn CLP 220	-25 / +110 Mobil SHC 630	-25 / +110 Klübersynth GEM 4-220 N	-25 / +110 Shell Omala S4 GX 220	-25 / +110 Carter SH 220
	-30 / 50			VG 150 [3]	-35 / +105 SEW GearOil Synth 150 E1 SEW 070040313			-30 / +95 Renolin Unisyn CLP 150	-30 / +100 Mobil SHC 629	-30 / +100 Klübersynth GEM 4-150 N	-30 / +100 Shell Omala S4 GX 150	-30 / +95 Carter SH 150
	-35 / 20			VG 68				-35 / +75 Renolin Unisyn CLP 68	-40 / +75 Mobil SHC 626		-40 / +75 Shell Omala S4 GX 68	
	-40 / 0			VG 32				-40 / +50 Renolin Unisyn OL32	-40 / +50 Mobil SHC 624			-40 / +50 Dacnis SH 32
	Standard -25 / 60	Ex	CLP HC - PSS	VG 220[3]	-30 / +110 SEW GearOil Synth 220 E1 SEW 070040313				-25 / +110 Mobil SHC 630			
	-30 / 50			VG 150 [3]	-35 / +105 SEW GearOil Synth 150 E1 SEW 070040313				-30 / +100 Mobil SHC 629			

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well!

 Für diese Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

Supplier Approval

SEW drives of the series

R../ K.7/ F../ K.9/ S../ HS../ W../ HW../ PS.F/ PS.C/ BS.F/ MGF..

Lubricant approvals – latest version: www.sew-eurodrive.de/lubricants

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
R.. RES K..7 KES HK.. F..	Standard -15 … 40	Ex	CLP HC - NSF H1	VG 460	-20 … +110 SEW GearOil Synth 460 H1 E1 SEW 070040313	-15 … +100 Cassida Fluid GL 460	-15 … +100 Optileb GT 460 SEW 070040313	-15 … +100 Cassida Fluid GL 460		-15 … +105 Klüberoil 4UH1-460 N		
	-25 … 30	Ex	CLP HC - NSF H1	VG 220	-30 … +90 SEW GearOil Synth 220 H1 E1 SEW 070040313	-25 … +80 Cassida Fluid GL 220	-25 … +80 Optileb GT 220 SEW 070040313	-25 … +80 Cassida Fluid GL 220		-25 … +80 Klüberoil 4UH1-220 N		
	-35 … 0	Ex	CLP HC - NSF H1	VG 68		-35 … +50 Cassida Fluid HF 68	-40 … +50 Optileb HY 68	-35 … +50 Cassida Fluid HF 68		-35 … +50 Klüberoil 4UH1-68 N		
	-40 … -10	Ex	CLP HC - NSF H1	VG 32		-40 … +30 Cassida Fluid HF 32	-40 … +30 Optileb HY 32	-40 … +30 Cassida Fluid HF 32		-40 … +30 KlüberSummit HySyn FG 32		
	Standard -15 … 40	Ex	CLP HC - NSF H1 - PSS	VG 460	-20 … +110 SEW GearOil Synth 460 H1 E1 SEW 070040313		-15 … +100 Optileb GT 460 SEW 070040313					
	-25 … 30	Ex	CLP HC - NSF H1 - PSS	VG 220	-30 … +90 SEW GearOil Synth 220 H1 E1 SEW 070040313		-25 … +80 Optileb GT 220 SEW 070040313					
	-20 … 40	Ex	E	VG 460				-20 … +80 Plantogear 460 S S2		-20 … +80 Klüberbio CA2-460 S2		

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well!

 Für diese Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

3. Helical-bevel gear units (K.9)

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
K.9	Standard -20 / 60	Ex	CLP PG (- PSS)	VG 460	-20 / +95 SEW GearOil Poly 460 E1 SEW 070040313					-20 / +95 Klübersynth GH 6-460		
	-15 / 80			VG 680						-15 / +115 Klübersynth GH 6-680		
	-25 / 40			VG 220	-25 / +70 SEW GearOil Poly 220 E1 SEW 070040313					-25 / +70 Klübersynth GH 6-220		
	-30 / 30			VG150	-30 / +60 SEW GearOil Poly 150 E1 SEW 070040313					-30 / +60 Klübersynth GH 6-150		
	Standard -20 / 60	Ex	CLP PG - NSF H1 (- PSS)	VG 460	-20 / +95 SEW GearOil Poly 460 H1 E1 SEW 070040313					-20 / +95 Klübersynth UH1 6-460		
	-15 / 80			VG 680						-15 / +115 Klübersynth UH1 6-680		
	-25 / 40	Ex		VG 220	-25 / +70 SEW GearOil Poly 220 H1 E1 SEW 070040313					-25 / +70 Klübersynth UH1 6-220		
	-30 / 30			VG 150	-30 / +60 SEW GearOil Poly 150 H1 E1 SEW 070040313					-30 / +60 Klübersynth UH1 6-150		

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well!

Für diese Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

4. Helical-worm gear units (S.., HS..)

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
S.. HS.. 	Standard 0 – 40		CLP	VG 680	0 / +80 SEW GearOil Base 680 S E1 SEW 070040313		0 / +80 Optigear BM 680	0 / +80 Renolin CLP 680 Plus SEW 070040313	0 / +80 Mobilgear 600 XP 680 SEW 070040313	0 / +80 Klüberoil GEM 1-680 N	0 / +80 Shell Omala SG 680	0 / +80 Carter EP 680
	-20 – 25			VG 150	-20 / +65 SEW GearOil Base 150 E1 / US1* SEW 070040313		-20 / +65 Optigear BM 150	-20 / +65 Renolin CLP 150 Plus SEW 070040313	-20 / +65 Mobilgear 600 XP 150 SEW 070040313	-20 / +65 Klüberoil GEM 1-150 N	-20 / +65 Shell Omala SG 150	-20 / +65 Carter EP 150
	Standard 0 – 40		CLP - PSS	VG 680	0 / +80 SEW GearOil Base 680 S E1 SEW 070040313			0 / +80 Renolin CLP 680 Plus SEW 070040313	0 / +80 Mobilgear 600 XP 680 SEW 070040313			
	-20 – 25			VG 150	-20 / +65 SEW GearOil Base 150 E1 / US1* SEW 070040313			-20 / +65 Renolin CLP 150 Plus SEW 070040313	-20 / +65 Mobilgear 600 XP 150 SEW 070040313			

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well!

* Viscosity as US version available on request.

 Für diese Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

Supplier Approval

SEW drives of the series

R../ K.7/ F../ K.9/ S../ HS../ W../ HW../ PS.F/ PS.C/ BS.F/ MGF..

Lubricant approvals – latest version: www.sew-eurodrive.de/lubricants

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
S.. HS.. 	Standard -20 80	Ex	CLP PG	VG 460 1)						-20 +115 Klübersynth GH 6-460		
	-25 60	Ex	CLP PG	VG 220 1)			-25 +90 Optigear Synthetic 800/220	-25 +95 Renolin PG 220	-25 +100 Mobil Glygoyle 220	-25 +100 Klübersynth GH 6-220	-25 +90 Shell Omala S4 WE 220	-25 +90 Carter SY 220
	-30 40	Ex	CLP PG	VG150 1)						-30 +85 Klübersynth GH 6-150		
	Standard -20 80	Ex	CLP PG - PSS	VG 460 1)						-20 +115 Klübersynth GH 6-460		
	-25 60	Ex	CLP PG - PSS	VG 220 1)						-25 +100 Klübersynth GH 6-220		
	-30 40	Ex	CLP PG - PSS	VG150 1)						-30 +85 Klübersynth GH 6-150		
	Standard -20 70	Ex	CLP PG - NSF H1 (- PSS)	VG 460 1)	-20 +110 SEW GearOil Poly 460 H1 E1 SEW 070040313					-20 +110 Klübersynth UH1 6-460		
	-25 40	Ex	CLP PG - NSF H1 (- PSS)	VG 220 1)	-25 +80 SEW GearOil Poly 220 H1 E1 SEW 070040313					-25 +80 Klübersynth UH1 6-220		
	-30 20	Ex	CLP PG - NSF H1 (- PSS)	VG 150 1)	-30 +65 SEW GearOil Poly 150 H1 E1 SEW 070040313					-30 +65 Klübersynth UH1 6-150		

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well!

 Für diese Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

Supplier Approval

SEW drives of the series

R../ K.7/ F../ K.9/ S../ HS../ W../ HW../ PS.F/ PS.C/ BS.F/ MGF..

Lubricant approvals – latest version: www.sew-eurodrive.de/lubricants

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
S.. HS..	Standard -15 / 60	Ex	CLP HC	VG 460				-15 / +100 Renolin Unisyn CLP 460	-20 / +105 Mobil SHC 634	-15 / +105 Klübersynth GEM 4-460 N	-15 / +105 Shell Omala S4 GX 460	-15 / +105 Carter SH 460
	-30 / 30			VG 150 3)				-30 / +70 Renolin Unisyn CLP 150	-30 / +75 Mobil SHC 629	-30 / +70 Klübersynth GEM 4-150 N	-30 / +75 Shell Omala S4 GX 150	-30 / +70 Carter SH 150
	-35 / 20			VG 68				-35 / +50 Renolin Unisyn CLP 68	-40 / +55 Mobil SHC 626		-40 / +50 Shell Omala S4 GX 68	
	-40 / 0			VG 32				-40 / +30 Renolin Unisyn OL32	-40 / +30 Mobil SHC 624			-40 / +30 Dacnis SH 32
	Standard -15 / 60	Ex	CLP HC - PSS	VG 460					-20 / +105 Mobil SHC 634			
	-30 / 30			VG 150 3)					-30 / +75 Mobil SHC 629			

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well!

 Für diese Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

Supplier Approval

SEW drives of the series

R../ K.7/ F../ K.9/ S../ HS../ W../ HW../ PS.F/ PS.C/ BS.F/ MGF..

Lubricant approvals – latest version: www.sew-eurodrive.de/lubricants

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
S.. HS..	Standard -15 / 40	Ex, Food	CLP HC - NSF H1	VG 460		-15 / +85 Cassida Fluid GL 460	-15 / +90 Optileb GT 460 SEW 070040313	-15 / +85 Cassida Fluid GL 460		-15 / +90 Klüberoil 4UH1-460 N		
	-25 / 30	Ex, Food	CLP HC - NSF H1	VG 220		-25 / +75 Cassida Fluid GL 220	-25 / +70 Optileb GT 220 SEW 070040313	-25 / +75 Cassida Fluid GL 220		-25 / +70 Klüberoil 4UH1-220 N		
	-35 / 0	Food	CLP HC - NSF H1	VG 68		-35 / +40 Cassida Fluid HF 68	-35 / +40 Optileb HY 68	-35 / +40 Cassida Fluid HF 68		-35 / +40 Klüberoil 4UH1-68 N		
	-40 / -10		CLP HC - NSF H1	VG 32		-40 / +25 Cassida Fluid HF 32	-40 / +20 Optileb HY 32	-40 / +25 Cassida Fluid HF 32		-40 / +25 KlüberSummit HySyn FG 32		
	Standard -15 / 40	Ex, Food	CLP HC - NSF H1 - PSS	VG 460			-15 / +90 Optileb GT 460 SEW 070040313					
	-25 / 30	Ex, Food	CLP HC - NSF H1 - PSS	VG 220			-25 / +70 Optileb GT 220 SEW 070040313					
	-20 / 40	Ex, Food	E	VG 460				-20 / +80 Plantogear 460 S S2		-20 / +80 Klüberbio CA2-460 S2		

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well!

 Für diese Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

5. Helical-worm gear units (S.7p)

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
S.7p 	Standard -20 / 80	Ex	CLP PG (-PSS)	VG 460 [1)]	-20 / +115 SEW GearOil Poly 460 E1 SEW 070040313							
	-25 / 60			VG 220 [1)]	-25 / +100 SEW GearOil Poly 220 E1 SEW 070040313							
	-30 / 40			VG150 [1)]	-30 / +85 SEW GearOil Poly 150 E1 SEW 070040313							

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well!

Für diese Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

6. Spiroplan gear units (W.., HW..)

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
W.. HW..	Standard -20 … 60	Ex	CLP PG (-PSS)	VG 460	-20 … +115 SEW GearOil Poly 460 W E1 SEW 070040313							
	-20 … 60	Ex	CLP PG NSF H1 (- PSS)	VG 460	-20 … +115 SEW GearOil Poly 460 H1 E1 SEW 070040313					-20 … +115 Klübersynth UH1 6-460		
	-30 … 20	Ex	CLP PG NSF H1 (- PSS)	VG150 [1)]	-30 … 65 SEW GearOil Poly 150 H1 E1 SEW 070040313					-30 … +65 Klübersynth UH1 6-150		
	-40 … 10	Ex	API GL5	SAE 75W90 (~VG 100)					-40 … +65 Mobil Synth Gear Oil 75 W90			

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well!

Für diese Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

7. PS.F gear units

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
PS.F	Standard -25 / 80	Ex	CLP PG (- PSS)	VG 220	-25 / +100 SEW GearOil Poly 220 E1 SEW 070040313					-25 / +100 Klübersynth GH 6-220		
	-20 / 80	Ex, food	CLP PG NSF H1 (- PSS)	VG 460	-20 / +100 SEW GearOil Poly 460 H1 E1 SEW 070040313					-20 / +100 Klübersynth UH1 6-460		
	-40 / 0	Ex	CLP HC	VG 32					-40 / +50 Mobil SHC 624			

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well!

 Für diese Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

8. PS.C gear units

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
PS.C	Standard -15 … 40		CLP	VG 220	-15 / +80 SEW GearOil Base 220 E1 / US1 SEW 070040313				-15 / +80 Mobilgear 600 XP 220 SEW 070040013			
	-40 … 0		CLP HC	VG 32					-40 / +50 Mobil SHC 624			
	-20 … 40		Fett / Grease	NLGI 00 [2]					-20 / +80 Mobilux EP 004			
	-20 … 40			NLGI 1						-20 / +80 Klübersynth UH1 14-151		

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well!

9. BS.F gear units

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
BS.F	Standard -25 … 60	Ex	CLP PG (- PSS)	VG 220	-25 / +100 SEW GearOil Poly 220 E1 SEW 070040313					-25 / +100 Klübersynth GH 6-220		
	-20 … 60	Ex	CLP PG NSF H1 (- PSS)	VG 460	-20 / +100 SEW GearOil Poly 460 H1 E1 SEW 070040313					-20 / +100 Klübersynth UH1 6-460		

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well!

Für diese Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

10. MGF gear units (MGF..-B, MGF..-C, MGF..-DSM, MGF../PG)

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
MGF..-C	Standard -25 / 60		CLP HC (- PSS)	VG 220	-30 / +110 SEW GearOil Synth 220 E1 SEW 070040313				-25 / +110 Mobil SHC 630			
	-30 / 50			VG 150	-35 / +105 SEW GearOil Synth 150 E1 SEW 070040313				-30 / +100 Mobil SHC 629			
	Standard -15 / 40		CLP HC - NSF H1 (-PSS)	VG 460	-20 / +110 SEW GearOil Synth 460 H1 E1 SEW 070040313		-15 / +100 Optileb GT 460 SEW 070040313					
	-25 / 30			VG 220	-30 / +85 SEW GearOil Synth 220 H1 E1 SEW 070040313		-25 / +80 Optileb GT 220 SEW 070040313					

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well!

Für diese Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

Supplier Approval

SEW drives of the series

R../ K.7/ F../ K.9/ S../ HS../ W../ HW../ PS.F/ PS.C/ BS.F/ MGF..

Lubricant approvals – latest version: www.sew-eurodrive.de/lubricants

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
MGF..-B MGF..-DSM	Standard -25 / 60		CLP HC	VG 220	-30 / +110 SEW GearOil Synth 220 E1 SEW 070040313			-25 / +110 Renolin Unisyn CLP 220	-25 / +110 Mobil SHC 630	-25 / +110 Klübersynth GEM 4-220 N	-25 / +110 Shell Omala S4 GX 220	-25 / +110 Carter SH 220
	-30 / 50			VG 150	-35 / +105 SEW GearOil Synth 150 E1 SEW 070040313			-30 / +95 Renolin Unisyn CLP 150	-30 / +100 Mobil SHC 629	-30 / +100 Klübersynth GEM 4-150 N	-30 / +100 Shell Omala S4 GX 150	-30 / +95 Carter SH 150
	Standard -25 / 60		CLP HC - PSS	VG 220	-30 / +110 SEW GearOil Synth 220 E1 SEW 070040313				-25 / +110 Mobil SHC 630			
	-30 / 50			VG 150	-35 / +105 SEW GearOil Synth 150 E1 SEW 070040313				-30 / +100 Mobil SHC 629			
	Standard -15 / 40		CLP HC - NSF H1	VG 460	-20 / +110 SEW GearOil Synth 460 H1 E1 SEW 070040313	-15 / +100 Cassida Fluid GL 460	-15 / +100 Optileb GT 460 SEW 070040313	-15 / +100 Cassida Fluid GL 460		-15 / +105 Klüberoil 4UH1-460 N		
	-25 / 30			VG 220	-30 / +90 SEW GearOil Synth 220 H1 E1 SEW 070040313	-25 / +80 Cassida Fluid GL 220	-25 / +80 Optileb GT 220 SEW 070040313	-25 / +80 Cassida Fluid GL 220		-25 / +80 Klüberoil 4UH1-220 N		
	Standard -15 / 40		CLP HC - NSF H1 - PSS	VG 460	-20 / +110 SEW GearOil Synth 460 H1 E1 SEW 070040313		-15 / +100 Optileb GT 460 SEW 070040313					
	-25 / 30			VG 220	-30 / +90 SEW GearOil Synth 220 H1 E1 SEW 070040313		-25 / +80 Optileb GT 220 SEW 070040313					

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well!

 Für diese Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés

Supplier Approval

SEW drives of the series

R../ K.7/ F../ K.9/ S../ HS../ W../ HW../ PS.F/ PS.C/ BS.F/ MGF..

Lubricant approvals – latest version: www.sew-eurodrive.de/lubricants

Produkt / Product	Umgebungstemperatur / Environment Temperature		Öltyp / Oil Type	ISO, SAE NLGI	SEW EURODRIVE	bremer & leguil	Castrol	FUCHS	Mobil	KLÜBER LUBRICATION	Shell	TOTAL
 MGF..-B /PG	Standard -25 / 60		CLP HC (- PSS)	VG 220					-25 / +110 Mobil SHC 630			
MGF..-B /PG	-30 / 50		CLP HC (- PSS)	VG 150					-30 / +100 Mobil SHC 629			
MGF..-DSM /PG MGF..-C /PG	Standard -15 / 40		CLP HC - NSF H1 (-PSS)	VG 460			-15 / +100 Optileb GT 460 SEW 070040313					
	-25 / 30		CLP HC - NSF H1 (-PSS)	VG 220			-25 / +80 Optileb GT 220 SEW 070040313					

NOTICE: The thermal application limits of radial oil seal materials (chapter 1.4) have to be considered as well.

 Für diese Unterlagen behalten wir uns alle Rechte vor / Copyright reserved / Tous droits de modification réservés